

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

XP-002268039

AN - 1973-25477U [18]

CPY - YUAS

DC - L03 X16

FS - CPI;EPI

IC - H01M35/02 ; H01M43/02

MC - L03-E01B

PA - (YUAS) YUASA BATTERY CO LTD

PN - JP48013774B B 00000000 DW197318 000pp

PR - JP19690000129 19691227

XIC - H01M-035/02 ; H01M-043/02

AB - J73013774 Title battery uses Zn as active anode material, Ag₂O as active cathode material and an alkali hydroxide soln. as electrolyte. Anode material is self-supporting. In the anode plate metallic Zn fibres are mixed with active anode material consisting of a Zn cpd. such as ZnO, or Zn(OH)₂, and the mixt. is formed into a plate together with an Ag wire. In an example, metallic Zn fibres having a length 1-20 mm and a dia. 10-40 mu were mixed with ZnO powder and water to obtain a paste-like mixt. The paste-like mixt. was coated over Ag leads and dried.

IW - ANODE PLATE ZINC ALKALI STORAGE BATTERY INCREASE DISCHARGE CHARGE CYCLE LIFE REDUCE SELF DISCHARGE

IKW - ANODE PLATE ZINC ALKALI STORAGE BATTERY INCREASE DISCHARGE CHARGE CYCLE LIFE REDUCE SELF DISCHARGE

NC - 001

OPD - 1969-12-27

ORD - 1900-00-00

PAW - (YUAS) YUASA BATTERY CO LTD

TI - Anode plate for zinc alkali storage battery - with increased discharge-charge cycle life and reduced self-discharge